



CTSP-SM8 “Embedded” HMS/DOCSIS Transponder for the TSP™

The “SM8” is a HMS/DOCSIS transponder that mounts on the face of the TSP power supply to provide an integrated, “embedded” status monitoring capability. Compatible with all TSP EM’s running v2.00 firmware or later, the SM8 provides not only the HMS power supply data set using the DOCSIS structure, it can be optionally provisioned with a VoIP/QAM test suite.



FEATURES

- Integrated “embedded” status monitoring solution
- SCTE-HMS 25-3 (HMS 022) compliant
- DOCSIS 2.0
- Monitors up to two battery strings
- Compatible with all TSP EM’s running v2.00 firmware or later
- Robust module based design protects electronics
- “Special” port allows monitoring/controlling of non-standard applications
- Single or Dual IP
- Multiple supplies can be monitored by one SM8 by connecting the HMS port to the HMS ports of the other supplies.
- Can be provisioned with the Electroline ENetMonitor™ VoIP/QAM test suite.

Model - No cables included

Myers Model #	Description
CTSP-SM8	TSP Embedded HMS/DOCSIS2.0 Transponder, Single IP Configuration
CTSP-SM8-2	TSP Embedded HMS/DOCSIS2.0 Transponder, Dual IP Configuration

Specifications***General**

Compliance:	DOCSIS 2.0
Data Set:	SCTE-HMS 25-3 (HMS 022/151)

RF

Return Frequencies (transmit)	5 to 42 MHz
Return Level Range:	+8 to +58 dBmV (modulation dependent)
Forward Frequencies (receive):	91 to 857 MHz, +/- 30KHz centered
Forward Level Range:	-15 to +15 dBmV (one channel)
Forward Total Input Power:	+30 dBmV maximum (full spectrum)
RF Port Impedance:	75 ohms
RF Port Return Loss:	> 6 dB

Ports and Connectors

RF Cable Interface:	Coaxial "F" type per ISO 169-24
Battery Interface:	Two 1x5 headers, one for each battery string
Battery Interface Cable:	Myers #: CTSPBCK-31, one 72" cable per string (must be purchased separately)
HMS Port:	HMS Data port complies with HMS022/151 data link layer specification
"Special" Port:	2x2 header with one each digital input and output

Environmental

Operating Temperature:	-40 to +70 degrees C (-40 to 158F)
Storage Temperature:	-50 to +85 degrees C (-40 to 176F)
Humidity:	up to 95% non-condensing

Mechanical

Weight:	0.64 Kg (1.4 lbs)
Dimensions (HxWxD):	66x148x51 mm (2.6 x 5.8 x 2 Inches)

*Specifications subject to change without notice



"Power Products by Power Professionals"

Myers Power Products, Inc.
44 S Commerce Way
Bethlehem, PA 18017

Aug-09

Tel: (610) 868-3500
Fax: (610) 868-8686
www.myerspowerproducts.com